# Zebra<sup>®</sup> ZXP Series 3<sup>™</sup> card printer



Loyalty P High Print Quality

# The value-packed choice for desktop card printing

Access

Advanced Design Features Employee ID Smart Encoding

The ZXP Series 3 direct-to-card printer offers several advanced features that provide great performance at an affordable price. Its compact footprint fits neatly into tight work spaces. With easy-to-use features like the Load-N-Go<sup>™</sup> ribbon cartridge and an LCD display with operating prompts, it requires little training and optimises uptime.

Zebra's ZRaster<sup>™</sup> host-based image processing enables highspeed printing while optimising print quality. And Zebra's new high-performance ribbons have an improved formulation specifically designed to support this high-speed, high-quality printing. Print one or both sides with high-quality, consistent monochrome or colour images.

The choice of connectivity options ensures that the ZXP Series 3 printer is easily integrated with local or networked systems, and with a full suite of buy-now or add-later encoding options, it is flexible enough to be suitable for a wide range of applications.

# **Key features:**

- Single- or double-sided direct-to-card printing
- Fast print speeds: up to 750 cards/ hour monochrome, 180 cards/hour full-colour YMCKO and 140 cards/hour full-colour YMCKOK
- Full encoding capabilities to meet a variety of markets and applications
- Excellent print quality with vibrant colours, and clear photos, text and bar codes
- Intuitive design for ease of use: simplifies training requirements
- Optional security features for instant-issuance card printing

# Ideal for:

- ID and access-control cards
- Personalised gift, membership and loyalty cards
- Event badges
- Instant-issuance financial cards
- Smart cards in travel, gaming and entertainment

# **Genuine Zebra supplies**

Genuine Zebra supplies meet stringent quality standards and are recommended for optimal printing quality and proper printer performance. The ZXP Series 3 card printer is designed to work only with Zebra True Colours<sup>®</sup> ix Series<sup>™</sup> high-performance ribbons.

For more information, visit www.zebra.com



## **Printing specifications**

- Dye-sublimation thermal-transfer direct-to-card
- ZRaster host-based image-processing technology
- Full-colour or monochrome printing
- Single- and double-sided printing
- 750 cards/hour monochrome single-sided
- 180 cards/hour full-colour YMCKO
- 140 cards/hour full-colour YMCKOK

• Edge-to-edge printing on standard CR-80 media NOTE: Print speed based on click to drop, average print coverage with USB connectivity, and cards/hour under certain conditions.

# **General specifications**

- Microsoft<sup>®</sup> Windows<sup>®</sup> drivers
- USB connectivity
- Covered 100-card feeder (30 mil/0.762mm)
- 50-card output hopper (30 mil/0.762mm)
- Zebra True Colours ix Series high-performance ribbons with intelligent media technology
- Auto-calibration of media
- Load-N-Go drop-in ribbon cartridge
- 16-character LCD display
- 300dpi (11.8 dots/mm) print resolution
- 32MB memory as standard
- Two-year warranty on printer
- Two-year warranty (unlimited passes) on original printhead
- Kensington<sup>®</sup> physical lock slot

# **Optional features**

- CardSense<sup>™</sup> single-card feed mode
- Built-in 10/100 Ethernet connectivity
- Lockable cover on card feeder and obscured output hopper
- ZebraCare<sup>™</sup> extended product-warranty programmes

# Encoding options & specifications

- Magnetic-stripe encoder ISO 7811 (new and re-encoded, tracks 1,2 and 3, high and low coercivity, stripe down, 30 mil/0.762mm card thickness)
- Smart-card contact station ISO 7816
- Combined MIFARE® contactless ISO 14443 and ISO 7816 contact encoder PC/SC-compliant

#### Bar codes & fonts

- Code 39, Code 128 with subsets B/C with and without check digit
- EAN 8 and EAN 13
- Interleaved 2-of-5
- UPC-A
- PDF417 2D bar code and other symbologies can be printed via Windows drivers
- TrueType<sup>®</sup> and other symbologies available via Windows driver

#### Software

 Microsoft Windows-certified printer drivers supported (all 32-bit- and 64-bit-compatible): XP, Windows Vista<sup>®</sup>, Windows Server<sup>®</sup> 2003, Windows Server 2008, Windows 7

#### **Supplies specifications**

- Zebra ix Series intelligent technology for
- authenticating and automating colour ribbonsMedia starter kit (single-sided): One YMCKO
- ribbon, 200 30 mil/0.762mm PVC cards, cleaning roll (one per ribbon)
- Cleaning supplies

#### True Colours ix Series ribbon

- YMCKO: 200 images/roll
- YMCKOK: 165 images/roll
- YMCKO 1/2 panel: 250 images/roll
- Monochrome: 1000 images/roll black, blue, green, gold, silver, red, white
- KdO: 500 images/roll
- KrO: 500 images/roll

## **Card compatibility**

- Card thickness: 30 mil/0.762mm
- Card size: CR-80 ISO 7810 format, Type ID-1, 54 x 86mm (2.12" x 3.38")
- Card material: PVC and composite
- Smart-card contact ISO 7816-1, 2, 3, 4
- Smart-card contactless MIFARE ISO 14443 A/B

## **Communications interfaces**

- USB V2.0 standard (cable included)
- Built-in 10/100 Ethernet optional

#### Electrical

- Single-phase AC power
- 90V~264V AC RMS and 47–63Hz (50–60Hz nominal)
- FCC Class A

## **Physical**

- Width 201mm (7.9")
- Height 236mm (9.3")
- Depth 368mm (14.5")
- Weight (printer only) 5.53kg (12.2lb)

# Environmental

- Operating temperature: 15°C/60°F to 30°C/86°F
- Storage temperature: -5°C/23°F to 70°C/158°F
- Operating humidity: 20% to 65% inclusive, non-condensing
- Storage humidity: 20% to 70% inclusive, non-condensing

# ZMotif<sup>™</sup> CardStudio<sup>™</sup> software

Zebra's ZMotif CardStudio is an easy-to-learn, easy-to-operate professional card-design and card-issuance software suite. It makes designing and printing professional photo ID cards and other cards easy, with basic to advanced features, and support for all Zebra card printers.

# For more information, visit www.zebra.com/cardstudio

#### \*Specifications subject to change without notice

©2011 ZIH Corp. CardSense, CardStudio, ix Series, Load-N-Go, ZebraCare, ZMotif, ZRaster and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head and True Colours are registered trademarks of ZIH Corp. All rights reserved. Kensington is a registered trademark of ACCO Brands Corporation. Microsoft, Windows, Windows Server and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries. MIFARE is a registered trademark of Philips Semiconductors Gratkorn GmbH Ltd. TrueType is a registered trademark of Apple Inc. All other trademarks are the property of their respective owners.



vww.zebra.com

# Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom **Telephone:** +44 (0)1628 556000 **Fax:** +44 (0)1628 556001 **E-mail:** mseurope@zebra.com **Web:** www.zebra.com

#### **Other EMEA Locations**

Europe: France, Germany, Italy, the Netherlands, Poland, Russia, Spain, Sweden, Turkey Middle East & Africa: Dubai, South Africa

Please recycle after use

12613L (05/11)