QuickSpecs



Nisca PR5350 High-Speed ID Card Printer

The NEW PR5350 offers a small foot-print, 24-bit color, 256-Grayscale, security lamination, encoding options and prints at the astounding speed of over 158 cards / hour.

The PR5350 joins the PR5300 series of printers and has the same Nisca quality, manufactured in their ISO certified production facility. The new printer offers brilliant 24-bit images printed on CR80 and CR79 cards with thicknesses ranging from 20 to 50 mils

The PR5350 is available with options for MagStripe, IC Chip, RFID reading and encoding; and also security lamination with the addition of the PR5302 laminator. Variable UV printing is also available for an additional security layer.

Summary of printer features:

- High-speed printing:
 - 158 cards per hour YMCO
 - 136 cards per hour YMCKO
 - 116 cards per hour YMCKO/K (dual sided print)
 - 104 cards per hour YMCK / K / Laminate (dual sided print / single side lamination)
 - 109 cards per hour YMCK / K / Laminate / Laminate (dual sided printing & lamination)***
- Full color edge to edge printing
- 300dpi dye-sublimation printing technology
- Industry leading 24-bit continuous tone printing
- 256-Grayscale
- Dual sided printing
- Dual sided lamination with alternating patch options
- USB 2.0 and Micro SCSI II output
- Full Windows compatibility
- IP Networking addressing via JetDirect device fully supported by Nisca drivers
- Automated cleaning mechanism
- MTBF 100.000 cards
- ISO9001 & ISO14001 Certifications

Summary of optional accessories:

- Security Overlamination w/ PR5302
 - 1mil Patch style
 - Thinfilm / foil
- Encoding
 - MagStripe
 - IC Contact
 - RFID
- Cleaning
 - Fully accessorized 10,000 print kit





QuickSpecs

PR5350 High Speed ID Card Printer Preliminary Specifications:

Specifications:

Printing system 300dpi, 24-bit continuous tone printing, 16.7million colors

Printing method Thermal transfer dye-sublimation

Print media PVC or polyester cards with polished PVC finish

Media size CR-80: 3.375" x 2.125 / 85.6 x 54mm

CR-79: 3.303" x 2.051" / 83.9mm x 52.1mm

Media thickness .020" (20mil) to .050" (50mil) / .508mm to 1.72mm

Print area Edge to edge Input hopper 100 cards Output hopper 100 cards

Image memory 16MB with parallel processing, four memory modes

System memory 2.25MB

Display LCD 16 character 2-line display shows printer status and

diagnostic prompts

Print ribbons options

Print speed* PR5350 YMCO Single side: 158 cards / hr

YMCKO Single side: 136 cards / hr YMCKO/K Dual side: 116 cards / hr YMCK/K w/ Lam: 104 cards / hr YMCK/K w/ Dual Lam: 109 cards/hr

Encoding options Offering integrated driver control for all encoding that includes:

- ISO standard Magstrip w/ dual high- and low-coercivity std.

- Contact IC Chip

- MIFARE®, Legic®, HID Prox, HID iCLASS

Interface USB 2.0 & SCSI II MTBF: 100,000 cards

Dimensions 16.57" (h) x 10.66" (w) x 13.03" (d) / 421 x 271 x 331mm

Weight 26.6lbs. / 13kg Operating temperature 65 to 80 F / 18 to 27 C

Power source AC100/240v 50/60Hz auto-switching

Agency listing UL/CE/FCC

Drivers Windows® compatible

Warranty 2-year return to depot service printer warranty, 1-year unlimited

prints print head warranty

Options: PR5302 Laminator

HID and $iCLASS^{\text{\tiny{0}}}$ are registered trademarks of HID Corporation. Other brands and names contained in this release are the property of their respective owners. For more information, please contact our authorized partner.

^{*} Print speed indicates approximate batch print speed and is measured from the time a card feeds into the printer to the time it ejects from the printer. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is depend on the size of the file, the CPU, the amount of PC memory, the interface (SCSI, USB, Parallel), and the amount of resources at the time of the print job.

^{**} RFID encoding capabilities differ depending on technology, please consult Team Nisca for more details.

^{*** 109} Cards per hour required two PR5302 laminators attached to one PR5350 Printer.